

Data Sheet

Item

1443



1. Product description:

Diamond mounted point (MT-4)

Dimensions (in): 3/4" x 9/16" x 1/4"


Dimensions (mm): 19 x 14.5 x 6.4

Specification: DVB35/40-MT8

Max. rpm: 40,000



MT-8



D = 19 mm
T = 14.5 mm
S = 6.4 mm



1. Application


- For grinding natural stone and concrete.
- Manufactured with high-quality vacuum-brazed diamond.
- Perfectly balanced.
- Excellent finish, ideal for both craft and industrial work.
- High performance and fast material removal.

2. Operating instructions

- Use wet.
- For use with a rotary tool (mototool).
- The distance between the rotary tool nozzle and the workpiece should not exceed 1/2" (12.7 mm).
- Mount the point and let it run idle for one minute to ensure it is not damaged.
- Apply moderate pressure, as excessive force may damage the diamonds.

3. Safety information

- Never exceed the maximum operating speed indicated on the label.
- Always wear full safety equipment (gloves, hearing protection, mask, and safety goggles).



Rotatory Tool

4. Handling

- The initial inspection must be carried out in the original packaging. If there is visible evidence of damage, the product should not be accepted.
- Handle the point carefully to avoid impacts or drops. If the point shows cracks, fractures, or any visible damage, it must not be used.

5. Storage

- Store the point in a dry, dust-free environment, preferably in its original packaging. Avoid prolonged exposure to hot, cold, or wet surfaces.

6. Packaging units

- 1 piece.

www.austromex.com.mx