

Data Sheet

Item

1327

TENAZIT®

1. Product description:

Seamless impregnated fiber wheel

Dimensions (in): 5" x 2" x 5/8"-11

Dimensions (mm): 125 x 50 x 15.9-11


Material: Aluminum Oxide

Specification: A MF Amarillo W1

Max. rpm: 3,800

Grit: Very Fine

Optimal RPM: 1,500



D = 125 mm
T = 50 mm
H = 15.9 mm - 11



1. Application

- For excellent polishing and finishing of bronze, copper, brass, stainless steel, and carbon steel parts.
- Seamless construction prevents marks on the overlap of polished surfaces.
- The impregnated fiber provides extended service life.
- Excellent for working on aluminum.
- Ideal for wide surface applications.
- Leaves a continuous satin finish.

2. Operating instructions

- Can be used wet or dry.
- For use with a satin finishing sander.
- Mount the wheel and let it run idle for one minute to verify that it is not damaged.
- Do not apply excessive pressure or strike the workpiece.

3. Safety information

- Never exceed the maximum speed indicated on the label.
- Always use safety guards.
- Always wear complete personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Improper use may cause serious injury.



Satin Finishing
Sander

4. Handling

- The initial inspection must be carried out in the original box. If there is visible evidence of damage to the packaging, the product should not be accepted.
- Handle the wheels carefully to prevent tearing or cracking. If a product breaks, loses a section, or shows signs of damage, it must not be mounted.

5. Storage

- Store the product on a flat surface at least 10 cm (4 in) above the ground, away from damp, cold, or hot surfaces, or any type of fluid.
- The ideal storage conditions for these products are 40–50% relative humidity and a temperature between 15 °C and 29 °C (59 °F and 84 °F).

6. Packaging units

- 1 piece.