Data Sheet


Item

1. Product description:

Seamless fiber wheel with shank

Dimensions (in):	3" x 2"x 1/4"
Dimensions (mm):	76 x 50 x 6.4
Material:	Aluminum Oxide
Specification:	ALO MEDIO
Max. rpm:	7,500
Grit:	Medium
Optimal RPM:	4,000





TENAZIT®













1. Application

- · For excellent polishing and finishing of bronze, copper, brass, stainless steel, and carbon steel parts.
- · Seamless construction prevents marks on the overlap of polished surfaces.
- Ideal for edges and external corners.
- · Leaves a continuous matte finish.

2. Operating instructions

- For use on a rotary tool.
- Mount the wheel and let it run idle for one minute to verify that it is not damaged.
- Do not apply excessive pressure or strike against the workpiece.

3. Safety information

- Never exceed the maximum speed indicated on the label.
- Always use safety quards.
- · Always wear complete personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- · Improper use may cause serious injury.



4. Handling

- The initial inspection must be carried out in the original packaging. If there is visible evidence of damage to the box, the merchandise should not be accepted.
- Handle the wheels carefully to prevent tearing or cracking. If a product breaks, loses a section, or is suspected to be damaged, it must not be mounted.

5. Storage

• Store the product on a flat surface at least 10 cm (4 in) above the ground, away from damp, cold, hot surfaces, or any type of fluid.

Ideal storage conditions are 40-50% relative humidity and a temperature between 15 °C and 29 °C (59 °F to 84 °F).

6. Packaging units

• 5 pieces.