

Data Sheet

Item

1414



1. Product description:

Diamond Wheel for Cutting and Profiling

Dimensions (in): 6" x 1/16" x 1-1/4"

Dimensions (mm): 150 x 1.6 x 31.75

Specification: D120R100CBD2D06P


Max. rpm: 6,400

Line: Oro

Max. speed: 50 m/s



Type 1A1R



D = 150 mm
T = 1.6 mm
H = 31.75 mm
X = 3.2 mm



Carbide

Certification

This wheel is certified by
the Organization for
the Safety of Abrasives.



Abrasive	Grit Size	Hardness	Concentration	Body	Bond	Internal Code	Identifier	Quality
Diamond	120 = Fine	R = Medium	100 = Medium	C = Steel	B = Resin	D2D	06 = Turquoise	P = Premium



1. Application

- For cutting, sharpening, and grooving of tungsten carbide tools.
- Designed for high-consumption users seeking greater performance.
- For users who prioritize profile retention and top performance.



CNC Machine

- If used on a machine or station without a containment guard, always operate with a safety guard.
- Always wear full protective equipment (gloves, hearing protection, mask, and safety glasses).
- Improper use may cause severe injury.
- For more detailed information, consult ANSI B7.1 and FEPA safety code.

4. Handling

- Initial inspection must be carried out in the original packaging. If there is visible damage to the package, the goods must not be accepted.
- Handle the wheel carefully in its original packaging to prevent impacts or drops. If the wheel shows cracks, fractures, or visible damage, it must not be used and the manufacturer should be notified.

5. Storage

- Store the wheel on a flat surface. Do not drop or strike it. Store in a clean, dry, dust-free environment, preferably in its original packaging. Do not expose for long periods to hot, cold, or wet surfaces.
- For more information, consult ANSI B7.1.

6. Packaging units

- 1 piece.

3. Safety information

- Always follow the manufacturer's recommended operating instructions.
- Never exceed the maximum operating speed of the product.

www.austromex.com.mx