Data Sheet

Item

1526

1. Product description:

Segmented Diamond Blade

Dimensions (in):	12" x 0.110" x 1"
Dimensions (mm):	300 x 3.0 x 25.4
Specification:	NARANJA BRONCE
Max. rpm:	5,100
# of Segments:	22
Segment Height:	7 mm
Line:	Bronce
Recommended Operating Speeds:	Reinforced Concrete: 25-35 (m/s) Cured Concrete: 35-40 (m/s)

DDD



D =	**300**	**mm**
T =	**3.0**	**mm**
H =	**25.4**	**mm**
W =	**7**	**mm**

Concrete

Certification

This diamond blade is certified by the Organization for the Safety of Abrasives.

Floor Saw

1. Application

• Diamond blade for cutting cured plain or reinforced concrete.
• Good performance.
• Features a drive pin hole.

2. Operating instructions

• Use with a high-power floor saw (25 HP or higher).
• Mount the blade following the direction of rotation indicated by the arrow on the blade and let it spin idle for one minute to verify it is not damaged.
• Designed for wet cutting applications. Prevent the product from overheating.
• Keep floors and work areas in good condition and free from obstructions.
• Use a moderate depth of cut and feed rate, as excessive cutting pressure may damage the diamonds.

3. Safety information

• Always use safety guards.
• Never exceed the maximum operating speed indicated on the label.
• Always wear appropriate personal protective equipment (PPE), including gloves, hearing protection, respiratory protection, and safety glasses.
• Do not use for grinding operations.
• Never attempt curved cuts.

4. Handling

• The initial inspection must be carried out while the product is still in its original packaging. If there is any visible evidence of damage, the product should not be accepted.
• Handle blades carefully to avoid impacts or drops. If a blade shows cracks, broken segments, or visible damage, it must not be mounted.

5. Storage

• Store the blade in a clean, dry environment, free from moisture, dust, and dirt, preferably in its original packaging. Avoid prolonged exposure to hot, cold, or wet surfaces.
• Store blades in a manner that prevents distortion of the steel core.
• Avoid resting the diamond segments against rigid surfaces that could damage them.
• If a diamond disc is stored at an angle, ensure that the entire face of the disc is supported, not just its edges.
• Store diamond blades in their original packaging on a flat surface. Small diamond blades may be suspended by their center holes.
• If blades are stored vertically, provide adequate lateral support.

6. Packaging units

• 1 piece.