

Item
1654


1. Product Description:

Flap Wheel with Metal Center


Dimensions (in):	6" x 2" x 1"
Dimensions (mm):	150 x 50 x 25.4
Abrasive:	Aluminum Oxide
Grit:	180
Specification:	A180B
Max. rpm:	5,800
Line:	Premium



RTFLAP



D = 150 mm
T = 50 mm
H = 25.4 mm



1. Application


- High-performance flap wheel for deburring, cleaning, and finishing flat or irregular surfaces of metal, cast iron, stainless steel, non-ferrous metals, paint, varnish, and plastic.
- Excellent for grinding while providing a uniform finish and high stock removal rate.

2. Operating instructions

- For use on a bench grinder or straight grinder.
- Mount the flap wheel according to the direction of rotation indicated by the arrow on the wheel, and allow it to run at no-load speed for one minute to verify that it is not damaged.
- Do not apply excessive pressure or strike the wheel against the workpiece.

3. Safety information

- Never exceed the maximum operating speed indicated on the product label.
- Always use appropriate safety guards.
- The use of appropriate personal protective equipment (PPE), including gloves, hearing protection, respiratory protection, and safety glasses, is recommended.
- Improper use may result in serious injury.



4. Handling

- Initial inspection should be performed while the product is in its original packaging. If there is visible evidence of damage, the product should not be accepted.
- Handle flap wheels carefully to prevent tearing or breakage. If the metal center is broken, abrasive flaps are detached, or the wheel is suspected of being damaged, it must not be mounted or used.

5. Storage

- Store flap wheels flat and at least 10 cm (4 in) above floor level, away from damp, cold, or hot surfaces and from any type of fluid.
- Ideal storage conditions are 40–50% relative humidity and a temperature between 15 and 29 °C (59–84 °F).

6. Packaging units

- 1 piece.