
Data Sheet

TENAZIT®

Item 1880



DL UGA



D = 125 mm



1. Product description:

Sanding Disc with ULTRAGRIP® backing system

Dimensions (in):	5"
Dimensions (mm):	125
Abrasive:	Carburo de Silicio
Grit:	3000
Specification:	TCCP-3000
Backing:	Foam
Line:	Kreator





Random Orbital Sander

1. Application

• For sanding and polishing paint, primer, and automotive bodywork.
• High efficiency helps reduce material consumption and working time.
• Excellent cutting speed.
• Provides precise control over the surface finish.
• Uniform wear across the entire disc.
• Ideal for automotive applications.
• For wet sanding applications.

2. Operating instructions

• Use with a random orbital sander.
• Mount the disc on the appropriate backing pad according to the attachment system.
• Start the machine with the disc in contact with the work surface.
• Do not apply excessive pressure or strike the disc against the workpiece.

3. Safety information

• Never exceed the maximum speed indicated on the label.
• Always use full personal protective equipment (gloves, hearing protection, mask, and safety glasses).
• Improper use may cause serious injury.

4. Handling

• Initial inspection must be carried out in the original packaging. If there is visible damage to the packaging, the product should not be accepted.
• Packages must not be exposed to hooks or sharp objects. They should not be stacked under excessive loads, as this may damage the product and cause breakage during use.

5. Storage

• All sanding products must be stored on pallets at least 10 cm above the floor, away from damp, cold, hot surfaces, or any type of fluid.
• Ideal storage conditions are 40–50% relative humidity and a temperature between 15 and 29 °C.

6. Packaging units

• 25 pieces.