

Data Sheet


Item
2127




1. Product description:

Segmented diamond blade

Dimensions (in):	14" x 0.125" x SC
Dimensions (mm):	350 x 3.2 x SC
Segment height:	10 mm
Specification:	PLATINO 4000 M*
Max. rpm:	4,400
Line:	Platino 4000



D = 350 mm
T = 3.2 mm
H = SC
W = 12 mm



1. Application

- For cutting green concrete and asphalt.
- Segments feature aligned and alternating diamond placement.
- Special bore design for green concrete cutting machines with medium aggregate materials.



Floor Saw

2. Operating instructions

- For wet use.
- Use with a floor saw.
- Mount the blade following the direction of rotation indicated by the arrow on the blade and let it spin idle for one minute to verify it is not damaged.
- Use moderate feed speed and cutting depth, as excessive pressure can damage the diamonds.

3. Safety information

- Always use safety guards.
- Never exceed the maximum operating speed indicated on the label.
- Always wear full personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Do not use for grinding operations.
- Never attempt curved cuts.

4. Handling

- The initial inspection must be carried out while the product is still in its original packaging. If there is any visible evidence of damage, the product should not be accepted.
- Handle blades carefully to avoid impacts or drops. If a blade shows cracks, broken segments, or visible damage, it must not be mounted.

5. Storage

- The blade should be stored in conditions free from moisture, dust, and dirt — preferably in its original packaging — and should not be exposed for long periods to hot, cold, or wet surfaces.

6. Packaging units

- 1 piece.