

Data Sheet

Item
2670




1. Product description:

Diamond polishing pads with
PULTRAGRIP® backing system.

Dimensions (in):	4"
Dimensions (mm):	100
Specification:	PAD PULIDO SECO/DIAM-50
Grit:	50
Max. rpm:	4000
Line:	Easy Cut®



DPUG



D = 100 mm



1. Application

- Designed for polishing curved surfaces of granite, marble, and terrazzo.
- Easy to handle, highly flexible, providing a consistent finish.

2. Operating instructions

- For dry use only.
- To be used on stone polishers.
- Mount the pad on backing pad item 1599 or 1499.
- Install on the machine and let it run idle for one minute to verify it is not damaged.
- Proceed with the polishing process.
- Apply moderate pressure. An excessive force can damage the diamond segments.

3. Safety information

- Always use safety guards.
- Never exceed the maximum operating speed indicated on the label.
- Always wear full personal protective equipment (PPE): gloves, hearing protection, dust mask, and safety goggles.



Stone
Polisher

4. Handling

- Initial inspection must be performed while the pads are in their original packaging. If visible damage is detected, the product must not be accepted.
- Handle pads with care to prevent impacts or drops. If fractured, with detached segments, or showing evident damage, the pad must not be mounted.

5. Storage

- Pads must be stored in conditions free of humidity, dust, and dirt, preferably in their original packaging. They should not be exposed for long periods to hot, cold, or wet surfaces.

6. Packaging units

- 5 pieces.