Data Sheet

TENAZIT®

Item

2883

1. Product description:

Knotted Wire End Brush with Shank

Diameter (D):	1-1/8" / 28 mm
Shank (d):	1/4" / 6.4 mm
Wire Diameter:	0.014" / 0.356 mm
Trim Length (H):	1-1/8" / 28 mm
Number of Knots:	12
Wire Material:	Steel
Specification:	12T 28MM LONG. AC. CARBON
Max. rpm:	20,000
Line:	Easy Cut®

CCTV



D = 28 mm
d = 6.4 mm
H = 28 mm



Rotary Tool

1. Application

• For cleaning metal surfaces and removing weld residue, rust, paint, varnish, plastic, and other surface imperfections.
• Also suitable for cleaning plastic and rubber molds, removing rubber residue, rust, paint, weld spatter, scale, slag, and dirt buildup from dies, pipe interiors, internal areas, and other hard-to-clean surfaces.
• Excellent for cleaning pipes and hard-to-reach areas.

2. Operating instructions

• Mount on a rotary tool or drill.
• Do not apply excessive pressure. These brushes are designed to work using only the wire tips; excessive pressure causes premature wear of the brush filaments.

3. Safety information

• Never exceed the maximum operating speed indicated on the brush.
• Always wear appropriate personal protective equipment, including gloves, hearing protection, a dust mask or respirator, and safety glasses.
• For additional information, refer to ANSI B165.1.
• Improper use may result in severe injury.

4. Handling

• Initial inspection should be performed while the brush is in its original packaging. If the brush is damaged, corroded, or deteriorated, do not use it and notify the supplier.
• Handle brushes carefully to prevent impacts or drops. If a brush is cracked, has lost a section, or is suspected to be damaged, it must not be mounted.

5. Storage

• Store the brush preferably in its original packaging in a clean and, above all, dry location. Prevent distortion of the filaments and avoid contamination from adhering to the brush.

6. Packaging units

• 10 pieces.