Data Sheet

TENAZIT®

Item
3236

1. Product description:

Sanding Disc with ULTRAGRIP® backing system

Dimensions (in):	3"
Dimensions (mm):	75
Abrasive:	Aluminum Oxide
Grit:	+/- 2000
Specification:	BU2000 VERDE
Backing:	Waterproof Latex
Line:	Kovax®

DL UGA



D = 75 mm

Paint Varnish Plastic

*Includes Interface Pad, Item 3239.

Angle Sander

1. Application

• For dry sanding and surface matting of new parts, existing paint, and surface preparation prior to painting.
• Excellent price-to-performance ratio.
• Suitable for virtually any surface, including concave and convex surfaces, thanks to the excellent flexibility provided by its innovative latex backing.
• Excellent for surface leveling without altering the material structure.
• Provides an extremely uniform finish without deep scratches, ideal for waterborne paints and high-solids clear coats.

2. Operating instructions

• Use with an angle sander. The use of Sander, Item 2510, is recommended.
• Mount the disc and allow it to run at no-load speed for one minute to verify that it is not damaged.
• For consistent finishes, the use of interface pads is recommended: Medium, Item 3238, or Soft, Item 3239.
• Do not apply excessive pressure or strike the disc against the workpiece.

3. Safety information

• Never exceed the maximum speed indicated on the label.
• Always use full personal protective equipment (gloves, hearing protection, mask, and safety glasses).
• Improper use may cause serious injury.

4. Handling

• Initial inspection must be carried out in the original packaging. If there is visible damage to the packaging, the product should not be accepted.
• Packages must not be exposed to hooks or sharp objects. They should not be stacked under excessive loads, as this may damage the product and cause breakage during use.

5. Storage

• All sanding products must be stored on pallets at least 10 cm above the floor, away from damp, cold, hot surfaces, or any type of fluid.
• Ideal storage conditions are 40–50% relative humidity and a temperature between 15 and 29 °C.

6. Packaging units

• 50 pieces.