

Item  
**3634**


## 1. Product description:

Full Tapered Cartridge Roll

|                         |                  |
|-------------------------|------------------|
| <b>Dimensions (in):</b> | 1/2" x 2" x 1/8" |
| <b>Dimensions (mm):</b> | 13 x 50 x 3.2    |
| <b>Abrasive:</b>        | Aluminum Oxide   |
| <b>Grit:</b>            | 80               |
| <b>Specification:</b>   | TUA4X- 80        |
| <b>Backing:</b>         | Poly-cotton      |
| <b>Structure:</b>       | Closed coat      |
| <b>Optimal RPM:</b>     | 12,000           |
| <b>Max rpm:</b>         | 20,000           |



CLC



D= 13 mm  
T = 50 mm  
H = 3.2 mm



## 1. Application

- For grinding, deburring, smoothing, and finishing metals, stainless steel, non-ferrous metals, and wood.
- Ideal for small areas, holes, or hard-to-reach zones such as corners, internal areas, small radii, blind holes, and operations where larger tools cannot fit.
- Their geometry allows them to work inside, outside, on, and around workpieces.
- Provides high precision in high-performance operations, as well as intermediate and final finishes.
- The abrasive grain composition also delivers strong sanding performance and long service life.

## 2. Operating instructions

- Use with a rotary tool.
- Use adapter item no. 1623.
- Mount the cartridge and let it run idle for one minute to ensure it is not damaged.
- Do not apply excessive pressure or subject it to impact against the workpiece.

## 3. Safety information

- Never exceed the maximum speed indicated on the label.
- Always use full personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Improper use may cause severe injury.



Rotary Tool

## 4. Handling

- Initial inspection must be carried out in the original packaging. If there is visible damage to the packaging, the product should not be accepted.
- Packages must not be exposed to hooks or sharp objects. They should not be stacked under excessive loads, as this may damage the product and cause breakage during use.

## 5. Storage

- All sanding products must be stored on pallets at least 10 cm above the floor, away from damp, cold, hot surfaces, or any type of fluid.
- Ideal storage conditions are 40–50% relative humidity and a temperature between 15 and 29 °C.

## 6. Packaging units

- 25 pieces.